



SPECIFICATIONS

FourStroke: 15-20 hp



HP / kW	20 / 14.7
Engine type	Inline 2
Displacement (CID/CC)	20.3 / 333
Full throttle RPM	5700 - 6200
Fuel induction system	Single Overhead Cam
Alternator amp / Watt	12/145 electric
Recommended fuel	87% octane / up to 10% ethanol
Recommended oil	25W-40 Synthetic Blend Mercury FC-W 10W-30 4-Stroke Marine Oil
Engine protection operator warning system	SmartCraft Engine Guardian
Starting	Electric Manual
Steering	Remote Tiller
Shaft length	15" / 381 mm 20" / 508 mm
Gearcase ratio	2.15:1
Dry weight *Lightest model available	99 lbs / 45 kg
CARB star rating	3
Bore and stroke	2.40 x 2.24" / 61 x 57 mm
Ignition	CDI w/electronic spark advance
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim system	Manual Power Tilt

Trim positions	6
Exhaust system	Through prop
Shallow water drive	Yes
Shallow water trim range (degrees)	16
Remote fuel tank standard (gal / L)	6.6 / 25
Color	Phantom Black
