

Model year 2010 SUN ODYSSEY

Sun Odyssey 39i




Sun Odyssey 39i Performance



Sun Odyssey 42i



Sun Odyssey 42i Performance



Certification conform with CE regulation.

	SO 39i	SO 39i Performance	SO 42i	SO 42i Performance
Overall length	11,86 m	11,86 m	12,85 m	12,85 m
Hull length	11,62 m	11,62 m	12,59 m	12,59 m
Waterline length	10,71 m	10,71 m	11,60 m	11,60 m
Beam	3,88 m	3,88 m	4,13 m	4,13 m
Displacement <i>light load with deep draft keel</i>	7330 kg	7330 kg	8410 kg	8410 kg
Standard draft <i>cast iron fin keel with elongated bulb and exterior epoxy barrier coat</i>	2,00 m	2,00 m	2,13 m	2,13 m
Standard keel weight	2280 kg	2280 kg	2553 kg	2553 kg
Shoal draft <i>cast iron fin keel with elongated bulb and exterior epoxy barrier coat</i>	1,50 m	-	1,60 m	-
Shoal keel weight	2450 kg	-	2781 kg	-
Performance keel draft <i>cast iron fin keel with elongated bulb and exterior epoxy barrier coat, profiled leading and trailing edges</i>	-	2,20 m	-	2,30 m
Performance keel weight	-	2100 kg	-	2520 kg
CE category	A9/B10/C12	A9/B10/C12	A9/B10/C14	A9/B10/C14
Architect/designer	M. Lombard	M. Lombard	M. Lombard	M. Lombard
Water <i>2 rotomolded tanks located under forward and aft berths with separate deck fills</i>	355 L	355 L	355 L	355 L
Fuel <i>rotomolded tank located under aft berth with deck fill</i>	130 L	130 L	130 L	130 L
Holding tank <i>rotomolded tank located in head compartment with valve for overboard discharge via gravity and deck fitting for pump out</i>	85 L	85 L	85 L	85 L
Fridge <i>fridge compartment with vertical access</i>	180 L	180 L	180 L	180 L

Classic mainsail <i>80% battened, high-tenacity Dacron cloth, Rutgerson® stainless steel eyes, 2 auto reefs</i>	36,3 m ²	-	39,1 m ²	-
Furling genoa <i>122% high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes</i>	34,2 m ²	-	42,4 m ²	-
Performance mainsail <i>Prestige series tri-radial with sandwich construction of double taffeta layers for form stability, 2 automatic reefs</i>	-	39 m ²	-	-
Performance Full Batten mainsail <i>Prestige series tri-radial with sandwich construction of double taffeta layers for form stability, 2 automatic reefs</i>	-	-	-	42 m ²
Performance furling genoa <i>125% tri-radial Prestige series with sandwich constructions of double taffeta layers for form stability and Sunbrella® UV luff protection, Rutgerson® stainless steel eyes</i>	-	38 m ²	-	47,5 m ²
Furling mainsail (optional) <i>high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes</i>	33,2 m ²	-	35 m ²	-
Spinnaker <i>optimal size for boat (not available from Jeanneau)</i>	97 m ²	120 m ²	115 m ²	135 m ²
Total sail area <i>for standard mast and sails</i>	70,5 m ²	77 m ²	81,5 m ²	89,5 m ²

■ Standard □ Option - Not available

		SO 39i	SO 39i Performance	SO 42i	SO 42i Performance
Sail handling	Lazy bag in Sunbrella® Captain Navy fabric with integrated lazy jacks	■	■	■	■
	Genoa winches 2 x Harken 46.2 self-tailing winches	■	■	■	-
	Genoa winches 2 x Harken 50.2 self-tailing winches	-	-	-	■
	Coachroof winches 2 x Harken 40.2 self-tailing winches	■	■	■	■
	Electric genoa winches 2 x Harken 46.2 STCE-H 12v self-tailing in place of standard winches	-	-	□	□
	Electric coachroof winch 1 x Harken 40.2 STCE-H 12v self-tailing in place of standard winch to port	□	□	PREFERENCE	PREFERENCE
	Genoa tracks adjustable Harken lead cars	■	-	■	-
	Genoa tracks adjustable Harken lead cars with adjustment line lead aft to cockpit jammer	-	■	-	■
	Winch handles 2 x Harken handles with ball-bearing grip	■	■	■	■
	Line jammers Spinlock, on both sides of coachroof with Harken return blocks	■	■	■	■
	Mainsheet traveller roof-mounted traveller with ball-bearing cars, control lines lead aft to cockpit	■	■	■	■
	Spinnaker deck hardware triple Spinlock jammer to starboard, 5 folding Wichard padeyes on side decks	PREMIERE	PREMIERE	■	■
	Asymmetrical spinnaker gear halyard, 2 sheets, tack line lead forward on deck, removable bowsprit on foredeck, Harken blocks	□	□	□	□
Symmetrical spinnaker gear halyard, 2 sheets, 2 guys, pole uphaul and downhaul, spinnaker pole and adjustable car for mast, Harken blocks	□	□	□	□	
Mast and Rigging	Classic mast SELDEN aluminium with double spreaders, spinnaker track mounted forward	■	-	■	-
	Performance mast SELDEN aluminium with double spreaders, spinnaker track mounted forward	-	■	-	■
	Standing rigging discontinuous 1x19 stainless steel wire	■	-	■	-
	Standing rigging discontinuous Dyform® stainless steel wire	-	■	-	■
	Backstay fixed, double	■	-	■	-
	Backstay adjustable via a block and tackle system and bridle-mounted car	-	■	-	■
	Genoa furler Facno® furler with attachment to stemhead fitting and furling line lead aft to roof winch	■	-	■	-
	Genoa furler Facno® racing series with removable drum, double sail slot and aerodynamic profile, mounted to stemhead fitting, furling line lead aft to roof winch	-	■	-	■
	Running rigging polyester topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets	■	-	■	-
	Running rigging Dyneema® mainsail halyard, genoa halyard, mainsheet, genoa sheets	-	■	-	■
Rigid boom vang with gas cylinder and control line lead aft to the cockpit	■	■	■	■	
Cockpit	Wood inlay on cockpit bench seating	■	■	■	■
	Wood cockpit floor inlay	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
	Wood side decks hand-laid wooden side decks	□	□	□	□
	Cockpit lockers 2 lockers under bench seats and 1 lazette locker under the port helm seat for technical access to steering system	■	■	■	■
	Liferaft locker located in dedicated compartment between helm seats	■	■	■	■
	Cockpit table folding injection-moulded fibreglass table with storage, cup holders, stainless steel handrail, courtesy lighting, 12v plug	■	■	■	■
	Solid wood cockpit table with all the same functions of above, but with wooden leaves and top and Sunbrella® Captain Navy cover	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
	Gas locker located in lazette locker under starboard helm seat, room for 2 gas bottles with connection to gas system and cut-off valve under stove in the galley	■	■	■	■
	Wheels 2 leather-covered steering wheels with compasses at each steering position and stainless steel grabrails	■	■	■	■
	Emergency tiller delivered with the boat, chrome fitting in cockpit floor	■	■	■	■
	Steering wheel covers Sunbrella® Captain Navy blue with zips for easy removal	□	□	□	□
	Instrumentation dedicated space for instruments within easy reach of helm positions, room for GPS chartplotter mounted at aft end of cockpit table with easy viewing from each helm	■	■	■	■
	Engine controls throttle and engine control panel mounted at starboard helm, engine panel includes fuel gauge, RPM gauge, warning lights, ignition	■	■	■	■
	Swim ladder folding stainless steel ladder mounted on transom	■	■	■	■
Cockpit shower retractable hot and cold water shower with tap	■	■	■	■	
Cockpit bimini Sunbrella® Captain Navy with stainless steel bows, retractable with storage cover	□	-	□	-	
Cockpit sprayhood wide Sunbrella® Captain Navy with vinyl windscreen with zip-out middle window for ventilation, retractable	□	□	□	□	
Anchor locker forward, lockable, room for anchor and tackle, integrated windlass area, holder for windlass handle	■	■	■	■	
Deck Hardware	Bow pulpit open, stainless steel with wood step, navigation lights and integrated wiring for lights	■	■	■	■
	Stern pulpits stainless steel with flag holder, buoy bracket and integrated wiring passage for GPS antenna	■	■	■	■
	Outboard engine bracket mounted on stern pulpit	□	□	□	□
	Electric windlass Quick 1000W combination rope and chain, vertical-mounted in the anchor locker, hand-held remote,	■	■	■	■
	Anchor roller double stainless steel fitting	■	■	■	■
	Anchoring kit Delta anchor 16kg with 28 meters of 10mm chain and 40 meters of 18mm line	□	□	-	-
	Anchoring kit Delta anchor 20kg with 32 meters of 10mm chain and 45 meters of 18mm line	-	-	□	□
	Lifelines double level of stainless steel lifelines, stainless steel stanchions	■	■	■	■
	Lifeline gates opening gates on each side	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
	Toerail wood profile with 6 integrated stainless steel chocks and drainage for side deck	■	■	■	■
	Wood rubrail for hull protection	□	□	□	□
	Cleats 4 x aluminium mooring cleats forward and aft	■	■	■	■
	Midship cleats 2 x aluminium cleats placed on side deck near midship chocks	PREMIERE	PREMIERE	PREMIERE	PREMIERE
	Mooring kit 6 fenders and 4 x docklines	□	□	□	□
Handrails sculpted, long wood handrails on coachroof for secure movement forward	■	■	■	■	

		SO 39i	SO 39i Performance	SO 42i	SO 42i Performance
Construction	Deck Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring	■	■	■	■
	Hull solid, hand-laid fibreglass, ISO gelcoat surface, protective barrier coat	■	■	■	■
	Structure 3 rd generation inner fibreglass grid, high-load zones cut out and relaminated, drainage system through structure, special emergency repair zone in keel area	■	■	■	■
Lighting	Flush mounted chromed brass ceiling lights in saloon, head compartments and cabins	■	■	■	■
	Chrome reading lights in aft cabin (s)	■	■	■	■
	Indirect halogen lighting under side decks in saloon and head compartments	■	■	■	■
	Gooseneck chart light mounted at nav station	■	■	■	■
Electrical	12 v alternator output	60 A	60 A	80 A	80 A
	Charge distributor/isolator	■	■	■	■
	Engine start battery capacity, batteries located under aft berths	110 Ah	110 Ah	110 Ah	110 Ah
	Domestic battery bank capacity, batteries located under aft berths	220 Ah	220 Ah	220 Ah	220 Ah
	Extra 110 Ah domestic battery	PREMIERE	PREMIERE	PREMIERE	PREMIERE
	Positive battery switch for engine and domestic bank and general cut-off switch mounted on panel in aft cabin	■	■	■	■
	Shorepower 230v inlet with differential breaker, one 230v plug per cabin, 230v plug in galley, saloon and nav station	PREMIERE	PREMIERE	■	■
	40A battery charger, multi-phase	PREMIERE	PREMIERE	PREMIERE	PREMIERE
	Electrical panel with 12v breakers, 230v breakers, 12v ammeter, 12v consumption meter, 12v charging meter (230v voltmeter on SO42i)	■	■	■	■
	12v plug per cabin and at nav station	■	■	■	■
Plumbing	230v stainless steel microwave, installed in galley cabinet	□	□	□	□
	Hot and cold pressurised water distributed through-out the boat via semi-rigid hose	■	■	■	■
	"Heavy-duty" water pump and accumulator tank for consistent water pressure	■	■	■	■
	40 litre hot water tank that is connected to engine heat exchanger and to 230v electrical system (option shorepower needed on SO39i)	■	■	■	■
	Chromed shower faucets in washrooms	■	■	■	■
	Electric bilge pump on float switch and manual dual-action pump in the cockpit	■	■	■	■
	Digital water level display	■	■	■	■
	Shower sumps equipped with individual electric pumps with filters and on-off switches	■	■	■	■
	Large manual pump marine toilets	■	■	■	■
	50 litre holding tank with gravity drain and deck fitting for forward starboard head (port aft head equipped with standard 85L tank)	-	-	□	□
Engine and Steering	Yanmar 3JH4E 40 HP, 29.4Kw latest generation of environmentally friendly engines	■	■	-	-
	Yanmar 4JH4E 54 HP, 39.6Kw latest generation of environmentally friendly engines	-	-	■	■
	Fully soundproofed engine compartment with engine access behind stairwell and from aft cabin	■	■	■	■
	Stainless steel propeller shaft 30mm diameter	■	■	■	■
	Fuel/water separator	■	■	■	■
	Built-in muffler, forced air ventilation and stainless steel exhaust fitting aft	■	■	■	■
	Fixed 3-blade bronze propeller	■	-	■	-
	Feathering propeller, 3-blade, Flex-o-Fold	-	■	-	■
	Bow thruster installed in a tunnel with dedicated battery	□	□	□	□
	Fibreglass rudder with solid stainless steel shaft	■	■	■	■
Patented self-aligning rudder bearings for lower friction	■	■	■	■	
Line cutting collar on shaft for extra protection against fouling	□	□	□	□	

Comfort features and options	Fixed hull ports with track-mounted curtains	4	4	4	4
	Opening cockpit and roof ports with curtains	2	2	4	4
	Lateral fixed windows with curtains	4	4	6	6
	Opening ports integrated into lateral windows	2	2	-	-
	Opening deck hatches forward-facing with sun blinds integrated into headliner	4	4	7	7
	Combination shade/insect screens for deck hatches	■	■	■	■
	CD/radio/MP3player in saloon	PREFERENCE	PREFERENCE	PREMIERE	PREMIERE
	Saloon stereo speakers x 2	■	■	■	■
	Cockpit speakers x 2, watertight	PREFERENCE	PREFERENCE	PREMIERE	PREMIERE
	Air Conditioning 230v 24000 BTU 2 units installed under saloon seating and in stern, vents in saloon and forward and aft cabins control panel and thermostat	-	-	□	□
	Forced air heating 1 unit 5500 BTU Webasto® diesel heater installed in stern, vents in aft cabin, saloon and head compartments (not available with Sun Odyssey 39i version 3 cabins/2 heads)	□	□	□	□

■ Standard □ Option - Not available

		SO 39i		SO 42i	
		2C1/H	3C1/H	2C2/H	3C2/H
Wood	Fine Teak® interior laminated panels with solid wood trim around galley, companionway and cabinetry, finished in satin UV stabilised varnish	■	■	■	■
	Laminate floorboards with light-coloured lines, finished in satin UV stabilised varnish, varnished edges	■	■	■	■
Forward cabin	Forward owner's cabin with central berth and storage forward of the berth	■	■	■	■
	Double berth, with wood trim, high-density foam mattress	2,05 x 1,85 m			
	Deep cabinet with shelves and hanging rod	■	■	■	■
	White vinyl lining on hull with lateral wood shelf	■	■	■	■
	Private forward head compartment with sink, clothes hook, mirror, towel holder, toilet paper holder, wastebasket, cabinet above sink and shower sump with grate and electric drainage pump	-	-	■	■
	Aft owner's cabin with access to starboard and large berth	■	-	■	-
	Double berth with high-density foam mattress	2,00 m x 1,75 m	-	2,00 m x 1,75 m	-
	Deep cabinet with shelves and hanging rod	■	-	■	-
	White vinyl lining on hull with lateral wood shelf	■	-	■	-
	Large head compartment aft with sink, separate plexiglass shower, clothes hook, mirror, towel holder, toilet paper holder, wastebasket, cabinet above sink and shower sump with grate and electric drainage pump, wood seat in shower	■	-	■	-
Aft cabin	Locker and technical compartment with access through head compartment, storage baskets, lighting and lots of extra space for storage under the exterior cockpit locker	■	-	■	-
	Twin aft cabins	-	■	-	■
	Double berths, high-density foam	-	2,00 m x 1,48 m	-	2,00 m x 1,48 m
	Deep cabinet with shelves and hanging rod per cabin	-	■	-	■
	White vinyl lining on hull with lateral wood shelf	-	■	-	■
	Head compartment aft with sink, shower, clothes hook, mirror, towel holder, toilet paper holder, wastebasket, cabinet above sink, shower sump with grate and electric drainage pump, access from saloon	-	■	-	■
	Navigation station full-function with general electrical panel, room for the latest in GPS chartplotters and bookshelf	■	■	■	■
	Sliding nav desk that can be placed in forward-facing or aft-facing position for increased seating with curved nav seat and storage underneath	■	■	■	■
	Deep navigation desk with storage	■	■	■	■
	Saloon with U-shaped seating area to starboard, wrap-around cushions and storage under seating area	■	■	■	■
Saloon dining table with wood fiddles, removable pedestal legs	■	■	■	■	
Saloon table with two fold-down leaves, bottle storage and conversion kit for double berth	PREMIERE	PREMIERE	PREMIERE	PREMIERE	
Storage cabinets along hull sides	■	■	■	■	
Lounge seating to port with plush cushions and upper storage cabinets	■	■	■	■	
Companionway with curved wood steps and non-slip strips	■	■	■	■	
Plexiglass companionway door with dedicated storage location in the aft starboard cabin	■	■	■	■	
Galley	Galley with double stainless steel sinks with covers, and reversible cutting board, laminated countertops, chrome plumbing fittings, storage cabinets and drawers	■	■	■	■
	L-galley to port with glass separator between galley counter and seating area	■	■	■	■
	Gimballed 2-burner stove with oven with stainless steel protection bar	■	■	■	■
	Luxury 2-burner stove with black finish, wood handle, stainless steel oven/broiler	PREMIERE	PREMIERE	PREMIERE	PREMIERE
	Single fridge box with freezer area, wire baskets, interior lighting comes on when door opened, 12v refrigeration and integrated compressor	■	■	■	■
Headroom	Forward cabin	1,88 m		1,90 m	
	Aft cabin (s)	1,95 m		1,96 m	
	Companionway	1,98 m		1,99 m	
	Saloon	1,95 m		1,97 m	
	Galley	1,93 m		1,95 m	

■ Standard □ Option - Not available C = Cabins H = Head

423 894 310 RCS La Roche sur Yon. Simplified inventory. This document is non contractual and we reserve the right to modify equipment or specification without advance notice. Updated June 2009. MORGANE - Les Herbiers

